

Specifications

Item	EO/IR Dual Sensor Gimbal														
Details	<u>Technical Specifications</u>														
	1. 3-axis Stabilized gimbal														
	<table><tr><td rowspan="3">Rotate range</td><td>Pitch(Min.)</td><td>±90°</td></tr><tr><td>Roll(Min.)</td><td>±45°</td></tr><tr><td>Yaw(Min.)</td><td>±150°</td></tr><tr><td rowspan="3">Jitter</td><td>Pitch(Max.)</td><td>±0.03°</td></tr><tr><td>Roll(Max.)</td><td>±0.03°</td></tr><tr><td>Yaw(Max.)</td><td>±0.03°</td></tr></table>	Rotate range	Pitch(Min.)	±90°	Roll(Min.)	±45°	Yaw(Min.)	±150°	Jitter	Pitch(Max.)	±0.03°	Roll(Max.)	±0.03°	Yaw(Max.)	±0.03°
	Rotate range		Pitch(Min.)	±90°											
			Roll(Min.)	±45°											
		Yaw(Min.)	±150°												
	Jitter	Pitch(Max.)	±0.03°												
		Roll(Max.)	±0.03°												
		Yaw(Max.)	±0.03°												
	2. EO(Electro-Optical) and IR(infrared) Dual sensor														
<table><tr><td>EO</td><td><ul style="list-style-type: none">- 2MP(Min.) CMOS Sensor- 30x optical zoom- Auto focust- 1080p/60 HDMI output- 1080p/30 H.264 video recording(onboard)- Auto object tracking function</td></tr><tr><td>IR</td><td><ul style="list-style-type: none">- Un-cooled long wave(8μm~14μm)- NETD : ≤ 55mK(@25°C)- MRTD : ≤ 660mK- 640×480, 15Hz(Min.)- Pixel size : 20μm(Max.)- 25mm lens- 4x digital zoom(Min.)- Color palette(Min.) : Black hot, white hot</td></tr></table>	EO	<ul style="list-style-type: none">- 2MP(Min.) CMOS Sensor- 30x optical zoom- Auto focust- 1080p/60 HDMI output- 1080p/30 H.264 video recording(onboard)- Auto object tracking function	IR	<ul style="list-style-type: none">- Un-cooled long wave(8μm~14μm)- NETD : ≤ 55mK(@25°C)- MRTD : ≤ 660mK- 640×480, 15Hz(Min.)- Pixel size : 20μm(Max.)- 25mm lens- 4x digital zoom(Min.)- Color palette(Min.) : Black hot, white hot											
EO	<ul style="list-style-type: none">- 2MP(Min.) CMOS Sensor- 30x optical zoom- Auto focust- 1080p/60 HDMI output- 1080p/30 H.264 video recording(onboard)- Auto object tracking function														
IR	<ul style="list-style-type: none">- Un-cooled long wave(8μm~14μm)- NETD : ≤ 55mK(@25°C)- MRTD : ≤ 660mK- 640×480, 15Hz(Min.)- Pixel size : 20μm(Max.)- 25mm lens- 4x digital zoom(Min.)- Color palette(Min.) : Black hot, white hot														
3. Gimbal System															
<ul style="list-style-type: none">- size(Max.) : 170(L) × 170(W) × 200(H)- Weight(Max.) : 1300 g- Power consumption(Max.) : 12W- Input Voltage : 12V~20V															